


EAN 4007841 055790



CE

energy saving

VDE



## **Function description**

max. 8 m

infrared sensor 180°

The new universal wizard. Lighting automation made easy: the IR 180 UP easy sensor switch is a revolutionary world first. It works in both as 2 and 3-wire installations and can switch all type of lamps ON and OFF. Simply replace existing flush-mounted switches – done! With 180° infrared sensor (8 m reach) and button for manual switching.

5 sec - 30 min

Teach mode

2 - 1000 lux

IP20

manual switch ON/OFF

## **Technical specifications**


Туре	Motion detectors	Twilight setting	2 – 1000 lx
Dimensions (L x W x H)	81 x 81 x 57 mm	Time setting	5 s – 30 Min.
lains power supply	220 – 240 V / 50 – 60 Hz	Switching output 1, resistive	200 W
Sensor Technology	passive infrared	Switching output 1, number of LED	<sup>s</sup> 4 pcs.
pplication, place	Indoors	/ fluorescent lamps	
stallation site	wall	Constant-lighting control	No
ype of installation	Concealed wiring	Basic light level function	No
lectronic scalability	No	With remote control	No
lechanical scalability	No	Interconnection	Yes
lounting height	0,90 – 2,20 m	IP rating	IP20
ptimum mounting height	1,1 m	Material	Plastic
etection angle	180 °	Ambient temperature	0 – 40 °C
ngle of aperture	90 °	Colour	white
neak-by guard	Yes	Colour, RAL	9010
, ,		IDs, certificates	VDE
each, radial	r = 3 m (14 m <sup>2</sup> )	Manufacturer's Warranty	3 years
each, tangential	r = 8 m (101 m <sup>2</sup> )		4007841055790
wilight setting TEACH	Yes	PU1, EAN	4007041055790

Motion detector IR 180 UP easy

EAN 4007841 055790





## **Detection Zone**



Mögliche Montagehöhe: 0,90 m – 2,20 m Orange: radial Schwarz: tangential

## **Dimension Drawing**







57 -

 $\vdash$ 

\_

https://www.steinel.de