


# Data sheet

Sensor-switched outdoor light

## L 400 S

black

EAN 4007841611019



### Function description

Simply classic, simply classy. Outdoor SensorLight L 400, ideal for building walls and entrance areas, for E 27 lamps, 240° angle of coverage, max. reach 12 m, basic light-level function, hand-blown crystal glass shade with decorative bubble effect.

### Technical specifications

Dimensions (L x W x H)	336 x 215 x 249,5 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Output	60 W
With lamp	No
Lamp	All-purpose lamp
Base	E27
With motion detector	Yes
Detection angle	240 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	r = 3 m (19 m <sup>2</sup> )
Reach, tangential	r = 12 m (302 m <sup>2</sup> )
Detection levels	5
Switching zones	276 switching zones

# Data sheet

Sensor-switched outdoor light

## L 400 S

black

EAN 4007841611019

### Technical specifications

Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	10 sec – 15 min
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	50 %
Continuous light	selectable, 4h
Impact resistance	IK00
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Glass transparent
Manufacturer's Warranty	5 years
Version	black
PU1, EAN	4007841611019

### Mood image

