


# Data sheet

Sensor-switched outdoor light

## L 585 S

black

EAN 4007841005535



### Function description

Individualist all round. Outdoor SensorLight L 585 S, ideal for building fronts and entrances, 180° angle of coverage, reach up to 12 m, selectable time and twilight threshold, sensor tilts through 70° for exact adjustment of the detection zone.

### Technical specifications

Dimensions (L x W x H)	307 x 215 x 228 mm
Mains power supply	230 – 240 V , 50 / 50 Hz
Sensor Technology	passive infrared
Output	60 W
With lamp	No
Lamp	All-purpose lamp
Base	E27
With motion detector	Yes
Detection angle	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	r = 3 m (14 m <sup>2</sup> )
Reach, tangential	r = 12 m (226 m <sup>2</sup> )
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	8 sec – 35 min

# Data sheet

Sensor-switched outdoor light

## L 585 S

black  
EAN 4007841005535

### Technical specifications

IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Glass transparent
Manufacturer's Warranty	3 years
Version	black
PU1, EAN	4007841005535

### Mood image

