


Data sheet

Photo-cell-controlled light

LN 1 LED

EAN 4007841649715



Function description

Slim and versatile. LED, naturally. STEINEL outdoor light LN 1 LED for permanently illuminating all sides of the building at night. 4,5 W STEINEL LED lighting system, 350 lm, light comes ON automatically at dusk, including adhesive house numbers, impact-resistant material (to IK 07).

Technical specifications

Dimensions (L x W x H)	195 x 300 x 53 mm
Mains power supply	230 – 240 V , 50 / 60 Hz
Sensor Technology	Light sensor
Output	4,5 W
Luminous flux	350 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No
Photo-cell controller	Yes
Twilight setting	5 – 200 lx
Impact resistance	IK07

Data sheet

Photo-cell-controlled light

LN 1 LED

EAN 4007841649715

Technical specifications

IP rating	IP54
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
includes sheet of self-adhesive numbers	Yes
PU1, EAN	4007841649715

Mood image

