


# Data sheet

Sensor-switched outdoor light

## L 22

Stainless steel

EAN 4007841009816



### Function description

The inviting light solution! Designer sensor-switched outdoor light L 22 with attractive stainless steel trim, ideal for building entrances and building fronts, 180° angle of coverage, reach up to 10 m, selectable time and twilight threshold, sensor tilts through 90°.

### Technical specifications

Dimensions (L x W x H)	286 x 162 x 85 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Output	60 W
With lamp	No
Lamp	All-purpose lamp
Base	E27
With motion detector	Yes
Detection angle	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	r = 3 m (14 m <sup>2</sup> )
Reach, tangential	r = 10 m (157 m <sup>2</sup> )
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	8 sec – 35 min

# Data sheet

Sensor-switched outdoor light

## L 22

Stainless steel

EAN 4007841009816

### Technical specifications

Impact resistance	IK07
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Stainless steel
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
Version	Stainless steel
PU1, EAN	4007841009816

### Mood image

