


Data sheet

Sensor-switched indoor light

RS LED D2

V3

EAN 4007841052539



Function description

Shining light. STEINEL high-frequency sensor-switched indoor light RS LED D2 with brushed stainless-steel surround, ideal for corridors, hallways, stairwells and bathrooms. 9,5 W with 795 lm, STEINEL LED lighting system, 360° high-frequency sensor with 3-8 m reach, switches light ON without a sound, with ambient light, night-light function and 4-hour manual override (3000 K).

Technical specifications

Dimensions (L x W x H)	300 x 300 x 65,5 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	9,5 W
Interconnection	No
Luminous flux	795 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °

Data sheet

Sensor-switched indoor light

RS LED D2

V3

EAN 4007841052539

Technical specifications

Electronic scalability	Yes
Mechanical scalability	No
Reach, tangential	Ø 8 m (50 m ²)
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 15 min
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Basic light level function percentage, from	10 %
Soft light start	Yes
Impact resistance	IK00
IP rating	IP20
Protection class	II
Ambient temperature	-10 – 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
PU1, EAN	4007841052539

Mood image

