


Data sheet

Sensor-switched LED floodlight

XLED PRO 240

Anthracite

EAN 4007841057695



Function description

Day-bright illumination throughout: the XLED PRO 240 sensor-switched outdoor floodlight. With fully swivelling LED flat panel and opal diffuser. 1830 lumens, 4000 K, 20 W. With a 240° infrared sensor for reliable motion detection over a reach of up to 12 m. Includes corner wall mount.

Technical specifications

Dimensions (L x W x H)	221 x 180 x 161 mm
Mains power supply	230 – 240 V
Mounting height max.	6,00 m
Sensor Technology	passive infrared
Output	20 W
Luminous flux	1830 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	60000 h
Drop in luminous flux in accordance with LM80	L70B10
With motion detector	Yes
Detection angle	240 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes

Data sheet

Sensor-switched LED floodlight

XLED PRO 240

Anthracite

EAN 4007841057695

Technical specifications

Reach, tangential r = 12 m (302 m²)

Photo-cell controller Yes

Impact resistance IK00

IP rating IP44

Protection class II

Housing material Plastic

Cover material Plastic, opal

Manufacturer's Warranty 5 years

Includes corner wall mount Yes

PU1, net weight 0,640 kg

Version Anthracite

PU1, EAN 4007841057695

Mood image

