

Motion detector

HF 3360

DALI - surface-mounted installation, square EAN 4007841011604



Function description

Perfection through and through. High-frequency motion detector HF 3360, ideal for basement corridors, stairwells, multi-storey car parks, installation height 2.8 m, 360° angle of coverage, reach 1 – 8 m (radial), detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls. Available either in round or square surface-mounted and concealed version.

Technical specifications

| Туре | Motion detectors |
|--------------------------|---|
| Dimensions (L x W x H) | 95 x 95 x 52 mm |
| Mains power supply | 220 – 240 V , 50 / 60 Hz |
| Sensor Technology | High frequency |
| Application, place | Indoors |
| Application, place, room | side room, stairwell, wc, washroom, multi-storey car park, underground car park, equipment room |
| Installation site | wall, ceiling, corner |
| Type of installation | Surface wiring |
| HF-system | 5,8 GHz |
| Electronic scalability | Yes |
| Mechanical scalability | No |
| Mounting height | 2,00 – 4,00 m |
| Optimum mounting height | 2,8 m |
| Detection | also through glass, wood and stud walls |
| Detection angle | 360 ° |
| Angle of aperture | 140 ° |
| Sneak-by guard | Yes |
| Reach, radial | Ø 8 m (50 m²) |



Motion detector

HF 3360

DALI - surface-mounted installation, square EAN 4007841011604

Technical specifications

| Reach, tangential | Ø 8 m (50 m²) |
|--|---|
| Twilight setting TEACH | Yes |
| Twilight setting | 2 – 1000 lx |
| Time setting | 5 sec – 15 min |
| Control output, DALI | Broadcast 1x30 electronic ballasts |
| Constant-lighting control | Yes |
| Basic light level function | Yes |
| Basic light level function in per cent | 10 – 50 % |
| Basic light level function time | 1-30 min, all night |
| Basic light level function percentage, from | 10 % |
| Basic light level function percentage, up to | 50 % |
| With remote control | No |
| Interconnection | Yes |
| IP rating | IP54 |
| Material | Plastic |
| Ambient temperature | -20 – 50 °C |
| Colour | white |
| Colour, RAL | 9003 |
| Manufacturer's Warranty | 5 years |
| Version | DALI - surface-mounted installation, square |
| PU1, EAN | 4007841011604 |



Motion detector

HF 3360

DALI - surface-mounted installation, square EAN 4007841011604

Mood image





Motion detector

HF 3360

DALI - surface-mounted installation, square EAN 4007841011604