

Motion detector

HF 3360

COM1 - surface-mounted installation, round
EAN 4007841033668



Function description

Perfection through and through. High-frequency motion detector HF 3360, ideal for basement corridors, stairwells, multi-storey car parks, installation height 2.8 m, 360° angle of coverage, reach 1 – 8 m (radial), detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls, heavy-duty relay for high switching capacity. Available either in round or square surface-mounted and concealed version.

Technical specifications

Type	Motion detectors
Dimensions (Ø x H)	126 x 52 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Application, place	Indoors
Application, place, room	side room, stairwell, wc, washroom, multi-storey car park, underground car park, equipment room
Installation site	wall, ceiling, corner
Type of installation	Surface wiring
HF-system	5,8 GHz
Electronic scalability	Yes
Mechanical scalability	No
Mounting height	2,00 – 4,00 m
Optimum mounting height	2,8 m
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	140 °
Sneak-by guard	Yes
Reach, radial	Ø 8 m (50 m ²)

Motion detector

HF 3360

COM1 - surface-mounted installation, round

EAN 4007841033668

Technical specifications

Reach, tangential	Ø 8 m (50 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	5 sec – 15 min
Switching output 1, resistive	2000 W
Switching output 1, number of LEDs / fluorescent lamps	8 pcs.
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	COM1 - surface-mounted installation, round
PU1, EAN	4007841033668

Mood image

