

Motion detector

IS 3360

COM1 - surface-mounted installation, square
EAN 4007841010478



Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential), large terminal compartment for easy installation, heavy-duty relay for high switching capacity. Available either in round or square surface-mounted and concealed version.

Technical specifications

| | |
|---|---|
| Type | Motion detectors |
| Dimensions (L x W x H) | 95 x 95 x 65 mm |
| Mains power supply | 220 – 240 V , 50 / 60 Hz |
| Sensor Technology | passive infrared |
| Application, place | outdoors, Indoors |
| Application, place, room | sports hall, side room, stairwell, wc, washroom, multi-storey car park, underground car park, warehouse, equipment room |
| Installation site | ceiling |
| Type of installation | Surface wiring |
| Switching zones | 1416 switching zones |
| Electronic scalability | No |
| Mechanical scalability | No |
| Mounting height | 2,50 – 4,00 m |
| Optimum mounting height | 2,8 m |
| Detection angle | 360 ° |
| Angle of aperture | 180 ° |
| Sneak-by guard | Yes |
| Capability of masking out individual segments | Yes |

Data sheet

Motion detector

IS 3360

COM1 - surface-mounted installation, square

EAN 4007841010478

Technical specifications

| | |
|--|---|
| Reach, radial | Ø 8 m (50 m ²) |
| Reach, tangential | Ø 40 m (1257 m ²) |
| Reach, presence | Ø 3 m (7 m ²) |
| Twilight setting TEACH | Yes |
| Twilight setting | 2 – 1000 lx |
| Time setting | 5 sec – 15 min |
| Switching output 1, resistive | 2000 W |
| Switching output 1, number of LEDs / fluorescent lamps | 8 pcs. |
| Constant-lighting control | No |
| Basic light level function | No |
| With remote control | No |
| Interconnection | Yes |
| IP rating | IP54 |
| Material | Plastic |
| Ambient temperature | -20 – 50 °C |
| Colour | white |
| Colour, RAL | 9003 |
| Manufacturer's Warranty | 5 years |
| Version | COM1 - surface-mounted installation, square |
| PU1, EAN | 4007841010478 |

Mood image

