Data sheet



Motion detector



DALI - surface-mounted installation, square EAN 4007841010560



Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential), large terminal compartment for easy installation. Available either in round or square surface-mounted and concealed version.

Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	95 x 95 x 65 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Application, place	outdoors, Indoors
Application, place, room	sports hall, side room, stairwell, wc, washroom, multi-storey car park, underground car park, warehouse, equipment room
Installation site	ceiling
Type of installation	Surface wiring
Switching zones	1416 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes

Data sheet



Motion detector

IS 3360

DALI - surface-mounted installation, square EAN 4007841010560

Technical specifications

Reach, tangentialØ 40 m (1257 m²)Reach, presenceØ 3 m (7 m²)Twilight setting TEACHYesTwilight setting2 – 1000 lxTime setting5 sec – 15 minControl output, DALIBroadcast 1x30 electronic ballastsConstant-lighting controlYesBasic light level function in per cent10 – 50 %Basic light level function percentage, from 10 %10 %	
Twilight setting TEACHYesTwilight setting2 – 1000 lxTime setting5 sec – 15 minControl output, DALIBroadcast 1x30 electronic ballastsConstant-lighting controlYesBasic light level functionYesBasic light level function in per cent10 – 50 %Basic light level function time1-30 min, all night	
Twilight setting2 – 1000 lxTime setting5 sec – 15 minControl output, DALIBroadcast 1x30 electronic ballastsConstant-lighting controlYesBasic light level functionYesBasic light level function in per cent10 – 50 %Basic light level function time1-30 min, all night	
Time setting 5 sec – 15 min Control output, DALI Broadcast 1x30 electronic ballasts Constant-lighting control Yes Basic light level function Yes Basic light level function in per cent 10 – 50 % Basic light level function time 1-30 min, all night	
Control output, DALI Broadcast 1x30 electronic ballasts Constant-lighting control Yes Basic light level function Yes Basic light level function in per cent 10 – 50 % Basic light level function time 1-30 min, all night	
Constant-lighting control Yes Basic light level function Yes Basic light level function in per cent 10 – 50 % Basic light level function time 1-30 min, all night	
Basic light level function Yes Basic light level function in per cent 10 – 50 % Basic light level function time 1-30 min, all night	
Basic light level function in per cent 10 – 50 % Basic light level function time 1-30 min, all night	
Basic light level function time 1-30 min, all night	
Desir linkt hand for a second on from	
Basic light level function percentage, from $$_{10\\%}$	
Basic light level function percentage, up 50 $\%$	
With remote control No	
Interconnection Yes	
IP rating IP54	
Material Plastic	
Ambient temperature-20 - 50 °C	
Colour white	
Colour, RAL 9003	
Manufacturer's Warranty 5 years	
Version DALI - surface-mounted installation, square	
PU1, EAN 4007841010560	

Data sheet



Motion detector



DALI - surface-mounted installation, square EAN 4007841010560

Mood image

