

# Hallway

IP - surface

EAN 4007841 066154

Article number 066154



max. 25 x 3 m



IP20



brightness



temperature



air humidity



2 - 4 m

5 years



manufacturer's  
warranty  
steinel-professional.de/garantie CE

## Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave).

## Technical specifications

|   |  |
|---|--|
| Type  | Presence detector                              |
| Dimensions (L x W x H)                        | 62 x 123 x 123 mm                              |
| Mains power supply                            | 18 – 55 V                                      |
| Power supply, detail                          | Passive PoE SELV, standard PoE (IEEE 802.3 af) |
| Sensor Technology                             | High frequency                                 |
| Application, place                            | Indoors  |
| Installation site                             | ceiling  |
| Installation                                  | Surface wiring                                 |
| Mounting height                               | 2,00 – 4,00 m                                  |
| Reach, radial                                 | 25 x 3 m (75 m <sup>2</sup> )                  |
| Reach, tangential                             | 25 x 3 m (75 m <sup>2</sup> )                  |
| HF-system                                     | 5,8 GHz  |
| Detection angle                               | 360 °  |
| Angle of aperture                             | 140 °  |
| Optimum mounting height                       | 2,8 m  |
| Mechanical scalability                        | No   |
| Sneak-by guard                                | Yes  |
| Capability of masking out individual segments | No   |

|                            |   |
|----------------------------|---|
| Electronic scalability     | Yes                                     |
| Detection                  | also through glass, wood and stud walls |
| Twilight setting TEACH     | No                                      |
| Constant-lighting control  | No                                      |
| Basic light level function | No                                      |
| Settings via               | Bluetooth, Web-Interface                |
| With remote control        | No                                      |
| Interconnection            | Yes                                     |
| IP-rating                  | IP20                                    |
| Material                   | Plastic                                 |
| Ambient temperature        | -20 – 50 °C                             |
| Application, room          | Indoors, corridor / aisle               |
| Colour                     | white                                   |
| Colour, RAL                | 9003                                    |
| Manufacturer's Warranty    | 5 years                                 |
| Version                    | IP - surface                            |
| PU1, EAN                   | 4007841066154                           |


# Hallway

IP - surface

EAN 4007841 066154

Article number 066154

## Detection Zone



Mögliche Montagehöhe: 2,00 m – 4,00 m  
Orange: radial und tangential

## Dimension Drawing

