

# Hallway

BT IPD (Slave) - surface

EAN 4007841 064563

Article number 064563



max. 25 x 3 m



2 - 4 m



IP54



2 - 2000 lux

5 years

manufacturer's  
warranty  
steinel-professional.de/garantie



CE

## Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave).

## Technical specifications

Type	Presence detector
Dimensions (L x W x H)	62 x 123 x 123 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	High frequency
Application, place	Indoors
Installation site	ceiling
Installation	Surface wiring
Mounting height	2,00 – 4,00 m
Reach, radial	25 x 3 m (75 m <sup>2</sup> )
Reach, tangential	25 x 3 m (75 m <sup>2</sup> )
HF-system	5,8 GHz
Detection angle	360 °
Angle of aperture	140 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No

Electronic scalability	Yes
Detection	also through glass, wood and stud walls
Twilight setting TEACH	No
Constant-lighting control	No
Basic light level function	No
Settings via	Bluetooth
With remote control	No
Interconnection	Yes
Type of interconnection	Master/slave
Material	Plastic
Ambient temperature	-20 – 50 °C
Application, room	Indoors, corridor / aisle
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	BT IPD (Slave) - surface
PU1, EAN	4007841064563


# Hallway

BT IPD (Slave) - surface

EAN 4007841 064563

Article number 064563


## Detection Zone



Mögliche Montagehöhe: 2,00 m – 4,00 m

Orange: radial und tangential

## Dimension Drawing



## Circuit diagram

